



VISTA VVRD

VANDAL RESISTANT CAMERA RANGE



IDEAL FOR APPLICATIONS SUCH AS:

- Prisons
- Schools
- Hospitals
- Car Parks
- Stair wells
- Lifts
- Airports
- Bus Depots
- Railway Stations

MAIN FEATURES:

- Both Monochrome and Colour cameras
- Discreet Design
- 4 -8mm DD Vari-focal lens
- Wall mount comes with a 3.6mm EI lens
- Vandal resistant housing

VANDAL RESISTANT CAMERAS

Able to withstand a blow from a 12lb sledgehammer, the Vandal Resistant Camera range from Vista is the ideal surveillance solution for monitoring areas prone to physical attack.

Available in a variety of different housings, the range has been designed to offer continuity in looks and features while delivering diversity in mounting styles and positioning.

The securely encased 4-8mm vari-focal Direct Drive lens (3.6mm EI for wall mounted versions) delivers crystal clear imagery for end users even under the most hostile of conditions. Both monochrome and colour versions are widely available.



THE UK'S PREMIER CCTV BRAND



TECHNICAL SPECIFICATIONS

	VVRDF4V8C	VVRD4V8C-LP	VVRD4V8C	VVRCW4V8C	VVRCM4V8C	VVRWM36C
MOUNT	Dome flush	Dome Surface	Dome Surface	Ceiling Wedge	Corner Mount	Wall Mount
SENSOR (CCD)	1/3" CCD					
TYPE	Colour					
RESOLUTION	470 TVL					
SENSITIVITY	2.8 lux with smoked cover, 1.0 lux without cover					
PIXELS	752 x 582					
COMPOSITE OUTPUT	1Vp.p					
SIGNAL TO NOISE RATIO	46dB AGC off					
ELEC. IRIS CONTROL	Off					
BLC	On 40% Cntr					
SHUTTER SPEED	Auto-1/50-1/100,000					
AGC	On					
SYNCHRONISATION	Internal					
GAMMA	On 0.45					
POWER SOURCE	12V DC +/-10%					
POWER CONSUMPTION	Max 2.4W					
WEIGHT	0.45Kg	0.59Kg	0.53Kg	0.97Kg	0.75Kg	0.7Kg
GROSS WEIGHT						
LENS OPTION	4-8 mm DD					3.6 MI
OPERATING TEMP.	-10deg C - 50 deg C					
OPERATING HUMIDITY	10-96% (non-condensing)					
DIMENSIONS (LXWXH)MM	120Dia x 91.5		114Dia x 94.5	172 x 103 x 92	124.2x 104.6 x 120	105 x 120 x 67.5
DIMENSIONS CAMERA	65 x 42 x 42					48 x 42 x 42
CONSTRUCTION	Aluminium					
WINDOW SIZE	86mm		88mm	58mm	40 x 50mm	
	VVRDF4V8M	VVRD4V8M-LP	VVRD4V8M	VVRCW4V8M	VVRCM4V8M	VVRWM36M
MOUNT	Dome flush	Dome Surface	Dome Surface	Ceiling Wedge	Corner Mount	Wall Mount
SENSOR (CCD)	1/3" CCD					
TYPE	Monochrome					
RESOLUTION	380 TVL					
SENSITIVITY	1.2 lux with smoked cover, 0.1 lux without cover					
PIXELS	512 x 582					
COMPOSITE OUTPUT	1Vp.p					
SIGNAL TO NOISE RATIO	46dB AGC off					
ELEC. IRIS CONTROL	Off					
BLC	On 40% Cntr					
SHUTTER SPEED	Auto-1/50-1/100,000					
AGC	On					
SYNCHRONISATION	Internal					
GAMMA	On 0.45					
POWER SOURCE	12V DC +/-10%					
POWER CONSUMPTION	Max 2W					
WEIGHT	0.45Kg	0.59Kg	0.53Kg	0.97Kg	0.75Kg	0.7Kg
GROSS WEIGHT						
LENS OPTION	4-8 mm DD					3.6 MI
OPERATING TEMP.	-10deg C - 50 deg C					
OPERATING HUMIDITY	10-96% (non-condensing)					
DIMENSIONS (LXWXH)MM	120Dia x 91.5		114Dia x 94.5	172 x 103 x 92	124.2x 104.6 x 120	105 x 120 x 67.5
DIMENSIONS CAMERA	65 x 42 x 42 mm					48 x 42 x 42 mm
CONSTRUCTION	Aluminium					
WINDOW SIZE	86mm		88mm	58mm	40 x 50mm	



VISTA NORBAIN HOUSE, ESKDALE ROAD, WINNERSH TRIANGLE, WOKINGHAM, BERKSHIRE. RG41 5TS
 TELEPHONE: +44 (0) 118 944 0123 FAX: +44 (0) 118 944 0999
 WEBSITE: WWW.VISTA-CCTV.COM